


- 04 RHEINZINK-Angled Standing Seam Facade,
- 16 RHEINZINK-Building Profile
 - i Connection/ termination profile
- 19 Separating Layer
 - d Breather membrane
- 20 Substructure
 - h WBP plywood or OSB Grade 3
Min. 18mm thick
- 21 Batten/ Squared Timber
 - Batten
 - Squared Timber
- 23 Supporting Structure
- 25 Thermal insulation
- 30 Ventilated Air Space



STANDARD DETAIL							
Side abutment +sealant tape -	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Title</td> <td style="text-align: left;">Scale</td> </tr> <tr> <td style="text-align: right;">Detail-Nr.</td> <td style="text-align: left;">Drawn</td> </tr> <tr> <td style="text-align: right;">Date</td> <td style="text-align: left;">gam</td> </tr> </table>	Title	Scale	Detail-Nr.	Drawn	Date	gam
Title	Scale						
Detail-Nr.	Drawn						
Date	gam						
0903030301012600001_GB_en	23.05.12						
<p>The detail describes an optional design in standard cases based on a European climate. Any user of this document is responsible to verify the feasibility of the solution with respect to the specific local situation and conditions. Using the documents provided by RHEINZINK is a service, which excludes liability for damages or claims of any kind. Contingent liability for malice or gross negligence is unaffected.</p>							